



UPS MAVERICK 750



Line Interactive UPS

- Microprocessor control guarantees high reliability
- Equipped with Boost and Buck AVR
- Green Power Function for energy saving
- DC Start Function
- Auto restart while AC recovery
- Compact size, Light Weight
- Provides AC Overload protection

Built-in AVR

Stabilizes output voltage and enhances battery life as UPS works on main mode on very high or low voltage conditions.

Green Power Function

Our UPS is equipped with green power function. For saving power and protecting battery, the method of deep discharging protection is adopted on inverter mode.

Audible Alarm

Audible alarm for backup / low battery / overload mode.



UPS MAVERICK 750

SPECIFICATION

Model	Maverick 750
Capacity	750VA / 360W
Input	
Nominal Voltage	230VAC
Normal Frequency	50/60Hz
Output	
On Battery Output Voltage	230±10%Vac
On Battery Output	50/60 Hz+/-1%
Overload Protection	Software
Battery	
Sealed Maintenance Free Lead Acid Battery	12V / 7AH x 1
Typical Recharge Time	8 Hours
Physical	
Dimensions D x W x H (mm)	87 x 165 x 276
Net Weight (kgs)	4.01Kg
Environment	
Operating Temperature	0°C to 40°C
Operating Relative Humidity	0 to 90%



LEDS INDICATOR

LED	ALARM	CONDITION
On	Off	Normal
Flash	Beep 1 time In Every 30 Seconds	Utility Failure-The UPS is providing battery power to outlets.
Flash	Beep 1 time In Every 2 Seconds	Utility Failure-The UPS is providing battery power. The rapid beeps indicate the battery will run out of power shortly.
Flash	Beep 1 time In Every 0.5 Second	Overload-Occurs when connected equipment exceeds the rating of the unit. Turn the UPS off and unplug at least one piece of equipment from the UPS.